

PRODUCT SPECIFICATION

Technical Specification	
Features	General Specification
Emergency Call	Operating Voltage 7.5V DC ±20%
Voice Encryption	Frequency Range UHF : 467.5125-467.675
Transmit Authority	Channel Spacing Analog 12.5 KHz
32 Channel Capacity	Frequency Stability ± 1.5 ppm
Voice Prompt	Operating Temperature - 25°C~ + 60°C
Programming Password	Battery Capacity Li-Ion 1600mAh DC 7.4V
High / Low Power Switch	Dimension (mm) 108.4*53.6*31.6 mm
Busy Channel Lock	Weight 220.4g (Include Battery)
Analog / Digital / PMR446	Durability IP54
Transmitter	
RF Power	Sensitivity (12dB SINAD)
FM Modulation	Intermodulation
Vocoder Type	Adjacent Channel Selectivity
Spurious and Harmonic	Spurious Response
SNR	Rated Audio Output Power
Max Frequency Deviation	Rated Audio Distortion
Rated Audio Distortion	Sensitivity (Digital)
	SNR

Receiver

Digital Two-Way Radio

Affordable & Reliable



VR630

- Ultra Long Battery Life
- Robust & Reliable
- Digital and Analog Dual Mode
- Crystal Clear Voice Quality

Standard Accessories:

